

GENERAL

UTV1100 - Trenching ROV Name

Road Transportable

Crane Launch

Features +1100hp of Jetting Power

> **Shallow Water Operations** Compact Deck Footprint

Manufacturer Sub - Atlantic

Year Built 2008

Latest Upgrades 2023

INSTRUMENTATION

Cameras 6 x Cameras

Lighting 8 x Dimmable

Pan and Tilt 1x P/T

> Fibreoptic Gyro **OA** Sonar

Bathy / Altimeter

MBES Surveillance

2x Scanning Profilers

Survey Grade Gyro (optional) Innova Multiplexer (optional)

Cable Tracking

System

Interface for TSS440 or TSS350



GENERAL TECHNICAL

Environ™ MV R 32 readily biode-Hydraulic Oil

gradable hydraulic oil

Pump Output Up to 16 Bar or 900m 3/h

1100hp/820kW (2 x 550 hp) at Pump Supply

1800 RPM

Up to 400 m/hr

Trenching Speed (Subject to soil conditions)

Maximum inclination angle 15°

Trenching Depth Up to 3m

Trench Width 1000 mm maximum

Up to 750 m/hr Survey Performance

Hydraulic 11kW 10 station Manifold

MAIN CHARACTERISTICS

Surface pumps rated for high

Operating Depth powered trenching from 0m to 200m

water depth / excursion

Width 4.7m

Dimensions Length 3.02m

Height 2.55m

440VAC, 60hz, 3-Phase, 63Amp x3 Power Requirements

Weight 4572 kg



+44 (0) 1670 281980